

JUN 16 2006

Appl. No. 10/787,485

Reply to Office Action of March 21, 2006

Amendments to the Claims:

This listing and version of the claims replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently amended): An integrated material transport system for an integrated circuit manufacturing factory, the system comprising:
 - a first material transport subsystem traveling at a first height;
 - a second material transport subsystem traveling at a second height; and
 - a predetermined material stocker having at least one ~~shared~~-material transfer port to be ~~used~~shared by both the first and second transport subsystems,

wherein the material transfer port has an elongated opening within a sidewall of the material stocker, and the elongated opening accommodates both the first material transport subsystem and the second material transport subsystem, and

~~wherein both the first and second material transport subsystems are serviced by an integrated rail subsystem for exchanging predetermined materials through the shared-material transfer port with the predetermined material stocker under a ceiling with a uniform height, the first material transport subsystem transfers material within a production bay and between at least two production bays, and the second material transportation subsystem provides transfers material between the at least two production bays.~~
2. (Canceled)
3. (Previously presented): The system according to claim 1 wherein the predetermined material stocker is located between the production bay and a main corridor.
4. (Original): The system according to claims 1 wherein the second material transport subsystem is an interbay material transport subsystem for providing material transfer between the predetermined material stocker and at least one other material stocker.

Appl. No. 10/787,485
Reply to Office Action of March 21, 2006

5. (Original): The system according to claim 1 wherein the second material transport subsystem is located outside of a production bay and within a main corridor.
6. (Canceled)
7. (Original): The system according to claim 1 wherein the material transfer port is located on a main corridor side of the predetermined material stocker.
8. (Original): The system according to claim 1 wherein the ceiling height is approximately 3 – 5 meters.
9. (Original): The system according to claim 1 wherein the integrated rail subsystem has two rails at different heights for servicing the first and second material transport subsystems simultaneously.
10. (Currently amended): An integrated material transport system for an integrated circuit manufacturing factory, the system comprising:
 - a first material transport subsystem having at least one over head transport module traveling at a first height for providing material transfer within a production bay and between at least two production bays;
 - a second material transport subsystem having at least one over head shuttle traveling at a second height for providing material transfer between the at least two production bays;
 - a predetermined material stocker having at least one ~~shared~~ material transfer port to be used/shared by both the first and second transport subsystems, wherein the material transfer port has an elongated opening within a sidewall of the material stocker, and the elongated opening accommodates both the first material transport subsystem and the second material transport subsystem; and
 - an integrated rail subsystem servicing both the first and second material transport subsystems at the first and second heights for exchanging predetermined materials through the ~~shared~~ material transfer port with the predetermined material stocker so that the factory does not

Appl. No. 10/787,485
Reply to Office Action of March 21, 2006

need different portions of its ceiling having different heights to accommodate the first and second material transport subsystems.

11. (Original)

12. (Original): The system according to claim 10 wherein the material transfer port is located on a main corridor side of the predetermined material stocker.

13. (Original): The system according to claim 10 wherein the factory has a ceiling height of approximately 3 – 5 meters.

14. (Original): The system according to claim 10 wherein the integrated rail subsystem has two rails at different heights for servicing the first and second material transport subsystems simultaneously.

15. (Currently amended): A method for integrating intrabay and interbay material transport systems in an integrated circuit manufacturing factory, the method comprising:

providing a first material transport system;

providing a second material transport system; and

providing a predetermined material stocker having at least one shared-material transfer port shared by both the first and second transport systems,

wherein the material transfer port has an elongated opening within a sidewall of the material stocker, and the elongated opening accommodates both the first material transport subsystem and the second material transport subsystem, and

wherein an integrated rail section services both the first and second material transport systems for exchanging predetermined materials through the ~~shared-material transfer port~~ with the predetermined material stocker under a ceiling with a uniform height, ~~the first material transport subsystem transfers material within a production bay and between at least two production bays, and the second material transportation subsystem transfers material between the at least two production bays.~~

Appl. No. 10/787,485
Reply to Office Action of March 21, 2006

16. (Canceled)
17. (Previously presented): The method according to claim 15 wherein the predetermined material stocker is located between the production bay and a main corridor.
18. (Original): The method according to claims 15 wherein the second material transport system is an interbay material transport system for providing material transfer between the predetermined material stocker and at least one other material stocker.
19. (Original): The method according to claim 15 wherein the second material transport system is located outside of a production bay and within a main corridor.
20. (Original): The method according to claim 15 wherein the material transfer port has a size sufficient to accommodate both the first material transport system and the second material transport system.
21. (Original): The method according to claim 15 wherein the material transfer port is located on a main corridor side of the predetermined material stocker.
22. (Original): The method according to claim 15 wherein the uniform ceiling height is approximately 3 – 5 meters.
23. (Original): The method according to claim 15 wherein the integrated rail section has two rail subsystems at different heights for servicing the first and second material transport systems simultaneously.

Appl. No. 10/787,485

Reply to Office Action of March 21, 2006

24. (Previously presented): The system of claim 1, wherein the first material transport subsystem is an overhead transport and the second material transport subsystem is an overhead shuttle system.

25. (New): The system according to claim 1, wherein the first material transport subsystem comprises an intrabay material transport subsystem for providing material transfer within a production bay or between the production bay and the predetermined material stocker.

26. (New) The method according to claim 15, wherein the first material transport system comprises an intrabay material transport system for providing material transfer within a production bay or between the production bay and the predetermined material stocker.